

IGS-6488XSFP

8 10/100/1000T + 8 100M/1G SFP + 4 1G/2.5G/10G SFP+ L2+ Industrial

Managed Ethernet Switch w/ Enhanced G.8032 Ring ; 24V/HV input models

- *Auto-sensing SFP/ SFP+ Uplink Cage*
- *Enhanced G.8032 ring covers multicast packets; MSTP 8/16* MSTI /RSTP ; support MRP ring**Miss-wiring avoidance & node failure protection*
- *User friendly UI, including auto topology drawing and DDM threshold monitoring with dB values***; Complete CLI*
- *Support LACP link aggregation, IGMP v3/router port, DHCP server & DHCP Option82; Port based DHCP distribution, Mac based DHCP server, SSH/SSL, HTTPS, INGRESS/EGRESS ACL L2/L3, TACACS+, QinQ*
- *USB port to backup, restore the configuration file and upgrade*
- *Protocol based VLAN** ; IPv4/IPv6 Subnet based VLAN***
- *Environmental Monitoring for temp., real input voltage, current*
- *Dual Input voltage 9~60VDC (24V model); Single input power 90~305VAC/120~430VDC (HV model)*
- *Wide range operation temperature (-E model):-40~75C/-40~167F; Fan-less design*



OVERVIEW

Lantech IGS-6488XSFP is a high performance L2+ (All Gigabit) Ethernet switch with 8 10/100/1000T + 8 100M/1G SFP + 4 1G/2.5G/10G SFP+ auto-sensing cage which provides L2 wire speed and advanced security function for network aggregation deployment. It delivers ITU G.8032 enhanced ring recovery less than 20ms in single ring. It also supports train ring, enhanced mode with easy configuration, comprehensive QoS, advanced security including INGRESS/EGRESS ACL L2/L3, TACACS+, SSH/SSL, Mac based DHCP server, DHCP Option 82, DHCP server, IGMPv1/v2/v3/router port, QinQ which are important features required in large network. The Cisco Discovery Protocol (CDP) and LLDP are supported for Ciscoworks to detect the switch info and show on L2 map topology.

Miss-wiring avoidance, node failure protection, Loop protection

The IGS-6488XSFP also embedded several features for stronger and reliable network protection in an easy and intuitive way. When the pre-set ring configuration failed or looped by miss-wiring, Lantech IGS-6488XSFP is able to alert with the LED indicator and disable ring automatically. Node failure protection ensures the Ethernet switches in a ring to survive after power breakout is back. The status can be shown in NMS when each Ethernet switch is back. Loop protection is also available to prevent the generation of broadcast storm when a dumb switch is inserted in a closed loop connection.

DHCP option 82 & Port based, Mac based DHCP,

Option66, IPv6 DHCP server****

DHCP server can assign dedicated IP address by MAC or by port (Port based for single switch), it also can assign IP address by port for multiple switches with single DHCP option82 server. DHCP Option66 server can offer IP address of TFTP server to DHCP client for VOIP application. Optional IPv6 address resolution for DHCP service can be supported.

User friendly GUI, Auto topology drawing

The user friendly UI, innovative auto topology drawing and topology demo makes IGS-6488XSFP much easier to get hands-on. The complete CLI enables professional engineer to configure setting by command line.

Enhanced G.8032 ring, 8/16 MSTI MSTP; MRP ring**

Lantech IGS-6488XSFP features enhanced G.8032 ring which can be self-healed in less than 20ms for single ring topology protection covering multicast packets. It also supports various ring topologies that covers enhanced ring and basic ring by easy setup than others. It supports MSTP that allows RSTP over VLAN for redundant links with 8/16** MSTI.

MRP (Media Redundancy Protocol) can be supported for industrial automation networks.

QoS and GVRP supported

It supports the QoS, GVRP for large VLAN segmentation.

IGMPv3, GMRP, router port, static multicast forwarding and multicast Ring protection

The unique multicast protection under enhanced G.8032 ring can offer immediate self-recovery instead of waiting for IGMP table timeout. It also supports IGMPv3, GMRP, router port and static multicast forwarding binding by ports for video surveillance application.

Editable configuration file; USB port for upload/download configuration

The configuration file of Lantech IGS-6488XSFP can be exported and edited with word processor for the other switches configuration with ease.

The built-in watchdog design can automatically reboot the switch when CPU is found dead.

The USB port can upload/download the configuration from/to USB dongle.

2DI/2DO for relay contact and event alerting by email** & traps

In case of event, the IGS-6488XSFP is able to send an email** to pre-defined addresses as well as SNMP Traps out immediately. It provides 2DI and 2DO. When disconnection of the specific port was detected; DO will activate the signal LED to alarm. DI can integrate the sensors for events and DO will trigger the alarm while sending alert information to IP network with email and traps.

Environmental monitoring for Ethernet switch inside information

The environmental monitoring can detect switch overall temperature, real input voltage and current where can send the SNMP traps and email** when abnormal.

24V/HV input voltage selection: dual 9V-60VDC (24V model) or single 90-305VAC/120-430VDC (HV model)

The is able to work from 9VDC to 60VDC (24V model). Or with single high power supply at 90-305VAC / 120-430VDC (HV model).

Industrial hardened design with high EFT and ESD protection

Lantech IGS-6488XSFP features high reliability and robustness coping with extensive EMI/RFI phenomenon, environmental vibration and shocks usually found in factory, substation, steel automation, aviation, mining and process control. Featured with relay contact alarm function, the IGS-6488XSFP is able to connect with alarm system in case of power failure or port disconnection. The IGS-6488XSFP also provides $\pm 2000V$ EFT and $\pm 4000VDC$ (Contact) / $\pm 8000VDC$ (Air) Ethernet ESD protection, which can reduce unstable situation caused by power line and Ethernet.

It is the best solution for Automation, transportation, surveillance, Wireless backhaul, Semi-conductor factory applications. The -E model can be used in extreme environments with an operating temperature range of $-40^{\circ}C$ to $75^{\circ}C$.


FEATURES & BENEFITS

- 8 10/100/1000T + 8 100M/1G SFP+ 4 1G/2.5G/10G SFP+ auto-sensing cage L2+ industrial managed Ethernet switch (Total 20 Ports Switch)
- Dual input from 9.5V-60VDC(24V model); HV single input from 90-305VAC/120-430VDC(HV model)
- Back-plane (Switching Fabric): 112Gbps
- 16K MAC address table
- DDM to support SFP diagnostic function***
 - Automatically convert the raw data into dB values for TX power/RX power, making it easier to measure the fiber distance
- 10KB Jumbo frame
- User friendly UI, auto topology drawing, topology demo, complete CLI for professional setting
- Enhanced G.8032 Ring protection in 20ms for single ring
 - Support various ring/chain topologies, including enhanced ring & basic ring
 - Enhanced G.8032 ring configuration with ease
 - Cover multicast and data packets protection
- Provides EFT protection $\pm 2000VDC$ for power line
- Supports $\pm 4000VDC$ (Contact) and $\pm 8000VDC$ (Air) Ethernet ESD protection
- Supports IEEE 802.1p Class of Service, per port provides 8 priority queues Port base, Tag Base and Type of Service Priority
- IEEE 802.1d STP, IEEE 802.1w RSTP, 802.1s MSTP VLAN redundancy with 8/16** MSTI
- 4K 802.1Q VLAN, Port based VLAN, GVRP, QinQ, QoS
- Supports IEEE 802.1ab LLDP, Cisco CDP; LLDP info can be viewed via Web/ Console
- DHCP server / client / DHCP Option 82 relay / DHCP Option 82 server; Port based DHCP server; DHCP Option 66; IPv6 address resolution for DHCP server**
- Mac based DHCP server to assign IP address that includes dumb Ethernet switches in DHCP network
- Bandwidth Control
 - Ingress packet filter and egress rate limit
 - Broadcast/multicast packet filter control
- Relay alarm output system events
- Miss-wiring avoidance
 - LED indicator
- TFTP/HTTP firmware upgrade
- System Event Log, SMTP Email** alert and SNMP Trap for alarm support; 32 RMON counters
- Security
 - SSL/SSH/INGRESS/EGRESS ACL L2/L3
 - Port Security: MAC address entries/Filter/static MAC-Port binding
 - IP Security: IP address security management to prevent unauthorized intruder.
 - TACACS+
 - Login Security: IEEE802.1X/RADIUS
 - HTTPS for secure access to the web interface


- Static multicast forwarding forward reversed IGMP flow with multicast packets binding with ports for IP surveillance application
- IGMP router port to assign query in ring and for reversed multicast video flow
- IGMPv1,v2,v3 with Query mode for multi media
- Dual image firmware support
- Factory reset button to restore setting to factory default
- Watchdog design to auto reboot switch when CPU is found dead
- Environmental monitoring for system real input voltage, current, ambient temperature
- Supports DIDO (Digital Input/Digital Output)
- Configuration backup and restoration
 - Supports text configuration file for system quick installation
 - USB port to upload/download configuration file by USB dongle
- IP30 metal housing with DIN rail and Wall-mount** design

DIMENSIONS (unit=mm)

24V model



HV model



SPECIFICATION

Hardware Specification

Standards IEEE802.3 10Base-T Ethernet
IEEE802.3u 100Base-TX

IEEE802.3ab 1000Base-T
IEEE802.3z Gigabit fiber
IEEE802.3x Flow Control and Back Pressure

| | |
|-----------------------|--|
| | IEEE802.3ad Port trunk with LACP IEEE802.1d Spanning Tree IEEE802.1w Rapid Spanning Tree IEEE802.1s Multiple Spanning Tree IEEE802.3ad Link Aggregation Control Protocol (LACP) IEEE802.1AB Link Layer Discovery Protocol (LLDP) IEEE802.1X User Authentication (Radius) IEEE802.1p Class of Service IEEE802.1Q VLAN Tag Back-plane (Switching Fabric): 112Gbps |
| Switch Architecture | |
| Mac Address | 16K MAC address table |
| Jumbo frame | 10KB |
| Connectors | 10/100/1000T: 8 x ports RJ-45 with Auto MDI/MDI-X function Mini-GBIC: 8x 100M/1G SFP + 4 x 1G/2.5G/10G SFP* auto-sensing cage with DDMI RS-232 connector: RJ-45 type USB x 1 Power & Relay connector: 1 x 6-pole terminal block DIDO : 1 x 6-pole terminal block |
| Network Cable | 10Base-T: 2-pair UTP/STP Cat. 3, 4, 5/ 5E/ 6 cable EIA/TIA-568 100-ohm (100m) 100Base-TX: 2-pair UTP/STP Cat. 5/ 5E/ 6 cable; EIA/TIA-568 100-ohm (100m) 1000Base-T: 4-pair UTP/STP Cat5E/6 cable; 10GBaseT:4-pair STP Cat6/6A/7 cable |
| Optical Cable | 1Gbps: Multi mode: 0 to 550 m, 850 nm (50/125 μm); 0 to 2 km, 1310 nm (50/125 μm) Single mode: 0 to 10 km/ 30 km/ 40 km, 1310 nm (9/125 μm); 0 to 50 km/ 60 km/ 80km/ 120 km, 1550 nm (9/125 μm) 2.5Gbps Multi mode: 0 to 300 m, 850 nm (50/125 μm); Single mode: 0 to 2 km/ 15 km/ 40 km, 1310 nm (9/125 μm); 0 to 40 km/ 80 km/ 100km, 1550 nm (9/125 μm) WDM 1Gbps: Single mode: 0 to 10 km/ 20 km/ 40 km/ 60 km, 1310 nm (9/125 μm); 0 to 80 km, 1490 nm (9/125 μm); 0 to 10 km/ 20 km/ 40 km/ 60 km/ 80 km, 1550 nm (9/125 μm) WDM 2.5Gbps Single mode: 0 to 5 km/ 20 km/ 40 km/ 60 km, 1310 /1550nm (9/125 μm); 0 to 80 km, 1490/1550 nm (9/125 μm) 10Gbps Multi mode: 0 to 300 m, 850 nm (OM3 50/125 μm); Single mode: 0 to 10 km/ 20 km, 1310 nm (9/125 μm); 0 to 40 km/ 80km/ 100 km, 1550 nm (9/125 μm) WDM 10Gbps Single mode: 0 to 10 km/ 20 km/ 40 km/ 60 km, 1270/1330 nm (9/125 μm); 0 to 80km, 1490/1550 nm (9/125 μm) |
| LED | Per unit: Power 1 (Green), Power 2 (Green), FAULT (Red); RM(Green) Ethernet port: Link/Activity (Green), Speed (Green); Mini-GBIC: Link/Activity (Green) |
| DI/DO | 2 Digital Input (DI) : Level 0: -30~2V / Level 1: 10~30V Max. input current:8mA 2 Digital Output(DO): Open collector to 40 VDC, 200mA |
| Operating Humidity | 5% ~ 95% (Non-condensing) |
| Operating Temperature | -20°C~60°C / -4°F~140°F (Standard model) -40°C~75°C / -40°F~167°F(-E model) |
| Storage Temperature | -40°C~85°C / -40°F~185°F |
| Power Supply | Dual DC input, 9~60VDC (24V model) Single HV input, 90~305VAC/120~430VDC (HV |

| | |
|-------------------------------|--|
| | model) |
| Power Consumption | 29W |
| Case Dimension | Metal case. IP-30, 74 (W) x 135 (D) x 152 (H) mm (24V model) 74 (W) x 165 (D) x 152 (H) mm (HV model) |
| Weight | 900 g |
| Installation | DIN Rail and Wall Mount** Design |
| EMI & EMS | FCC Class A, CE EN55032 Class A, CE EN55024, CE EN61000-4-2, CE EN61000-4-3, CE EN61000-4-4, CE EN61000-4-5, CE EN61000-4-6, CE EN61000-4-8, CE EN61000-6-2, CE EN61000-6-4 |
| Stability Testing | IEC60068-2-32 (Free fall), IEC60068-2-27 (Shock), IEC60068-2-6 (Vibration) |
| MTBF | 591,245 (Hrs) (standards: IEC 62830) |
| Warranty | 5 years |
| Software Specification | |
| Management | SNMP v1 v2c, v3/ Web/Telnet/CLI |
| SNMP MIB | RFC 1215 Traps MIB*, RFC 1213 MIBII RFC 1158 MIBII RFC 1157 SNMP MIB, RFC 1493 Bridge MIB* RFC 1573 IF MIB RFC 2674 VLAN MIB*, Partial RFC 1757 RMON, RFC 2674 Q-Bridge MIB*; Bridge MIB, Private MIB |
| ITU G.8032 | Support ITU G.8032 v2/2012 for Ring protection in less than 20ms for self-heal recovery (single ring enhanced mode) Support basic single ring & enhanced ring Enhanced G.8032 ring configuration with ease Cover multicast & data packets protection |
| User friendly UI | <ul style="list-style-type: none"> ■ Auto topology drawing ■ Topology demo ■ Complete CLI for professional setting |
| Port Trunk with LACP | <ul style="list-style-type: none"> ■ LACP Port Trunk: 10 Trunk groups |
| LLDP | Supports LLDP to allow switch to advise its identification and capability on the LAN |
| CDP | Cisco Discovery Protocol for topology mapping |
| Environmental Monitoring | System status for real input voltage, current and ambient temperature to be shown in GUI and sent alerting if any abnormal status |
| VLAN | Port Based VLAN IEEE 802.1Q Tag VLAN (256 entries)/ VLAN ID (Up to 4K, VLAN ID can be assigned from 1 to 4096.) GVRP, QinQ, QoS, Protocol based VLAN** ; IPv4/IPv6 Subnet based VLAN** |
| IPv6/4 | Present |
| Spanning Tree | Supports IEEE802.1d Spanning Tree and IEEE802.1w Rapid Spanning Tree, IEEE802.1s Multiple Spanning Tree 8/16** MSTI |
| Quality of Service | The quality of service determined by IPv4 Type of service, IPv4 Differentiated Services Code Points - DSCP |
| Class of Service | Support IEEE802.1p class of service, per port provides 8 priority queues |
| IP Security | Supports 10 IP addresses that have permission to access the switch management and to prevent unauthorized intruder. |
| Login Security | Supports IEEE802.1X Authentication/RADIUS |
| Port Mirror | Support 3 mirroring types: "RX, TX and Both packet" |
| Network Security | Support 10 IP addresses that have permission to access the switch management and to prevent unauthorized intruder. 802.1X access control for port based and MAC based authentication/static MAC-Port binding Ingress/Egress ACL L2/L3 SSL/ SSH for Management |

| | |
|-----------------------------|--|
| | HTTPS for secure access to the web interface TACACS+ for Authentication |
| IGMP | Support IGMP snooping v1,v2,v3; 256 multicast groups; IGMP router port ; IGMP query; GMRP |
| Static multicast forwarding | Static multicast forwarding forward reversed IGMP flow with multicast packets binding with ports for IP surveillance application |
| Bandwidth Control | Support ingress packet filter and egress packet limit. The egress rate control supports all of packet type. Ingress filter packet type combination rules are Broadcast/Multicast/Flooded Unicast packet, Broadcast/Multicast packet, Broadcast packet only and all types of packet. The packet filter rate can be set an accurate value through the pull-down menu for the ingress packet filter and the egress packet limit. |
| Flow Control | Supports Flow Control for Full-duplex and Back Pressure for Half-duplex |
| System Log | Supports System log record and remote system log server |
| SMTP | Supports SMTP Server and 8 e-mail accounts for receiving event alert |
| Relay Alarm | Provides one relay output for port breakdown, power fail and alarm. Alarm Relay current carry ability: 1A @ DC24V |
| Protection | <ul style="list-style-type: none"> ■ Miss-wiring avoidance ■ Node failure protection ■ Loop protection |
| SNMP Trap | Up to 5 trap stations; trap types including: <ul style="list-style-type: none"> ● Device cold start ● Authorization failure |

| | |
|-----------------------------------|--|
| | <ul style="list-style-type: none"> ● Port link up/link down ● DI/DO open/close ● Typology change(ITU ring) ● Power failure ● Environmental abnormal |
| DHCP | <ul style="list-style-type: none"> ● Provide DHCP Client/ DHCP Server/DHCP Option 82/Port based or VLAN based DHCP distribution (DHCP relay agent); DHCP Option 66; IPv6 address resolution for DHCP server |
| Mac based DHCP Server | Assign IP address by Mac that can include dumb switch in DHCP network |
| DNS | Provide DNS client feature and support Primary and Secondary DNS server. |
| SNTP | Supports SNTP to synchronize system clock in Internet |
| Firmware Update | Supports TFTP firmware update, TFTP backup and restore; HTTP firmware upgrade |
| Configuration upload and download | Supports text configuration file for system quick installation; Support factory reset button to restore all settings back to factory default; USB for auto restore/backup configuration file |
| Dual Image Firmware | Support dual image firmware function |

*Future release
**Optional
***Optional DDM
SFP required

ORDERING INFORMATION

- **IGS-6488XSFP-24V.....P/N: 8350-872**
8 10/100/1000T + 8 100M/1G SFP + 4 1G/2.5G/10G SFP+ Auto sensing cage L2+ Industrial Managed Ethernet Switch; -20°C to 60°C; Environmental Monitoring; dual input 9.5V~60V
- **IGS-6488XSFP-24V-E.....P/N: 8350-873**
8 10/100/1000T + 8 100M/1G SFP + 4 1G/2.5G/10G SFP+ Auto sensing cage L2+ Industrial Managed Ethernet Switch; -40°C to 75°C; Environmental Monitoring; dual input 9.5V~60V
- **IGS-6488XSFP-HV.....P/N: 8350-874**
8 10/100/1000T + 8 100M/1G SFP + 4 1G/2.5G/10G SFP+ Auto sensing cage L2+ Industrial Managed Ethernet Switch; -20°C to 60°C; Environmental Monitoring; Single high power 90~305VAC/120~430VDC
- **IGS-6488XSFP-HV-E.....P/N: 8350-875**
8 10/100/1000T + 8 100M/1G SFP + 4 1G/2.5G/10G SFP+ Auto sensing cage L2+ Industrial Managed Ethernet Switch; -40°C to 75°C; Environmental Monitoring; Single high power 90~305VAC/120~430VDC

OPTIONAL ACCESSORIES

DIN Rail Power

- **NDR-240-48** 240W (48V 5A) Single Output Industrial Din Rail Power; 90-264VAC / 127-370VDC Input Range; Cooling by free air convection; RoHS2 ; Operating Temp. -20°C~70°C (ambient, derating each output at 2.5% per degree from 50°C ~ 70°C)
- **NDR-120-48** 120W (48V 2.5A) Single Output Industrial Din Rail Power; 90-264VAC / 127-370VDC Input Range; Cooling by free air convection; RoHS2 ; Operating Temp. -20°C~70°C (ambient, derating each output at 2.5% per degree from 50°C ~ 70°C; For 115VAC, please refer to derating curve on NDR-120 Series datasheet)

Mini GBIC (SFP)

- | | |
|--|--|
| ■ 8330-162X MINI GBIC 1000SX (LC/0.5km) Transceiver | ■ 8330-189 LTSFP-1000BX-10KM Transceiver (WDM 1550) |
| ■ 8330-163X MINI GBIC 1000SX2 (LC/2km) Transceiver | ■ 8330-186 LTSFP-1000BX-20KM Transceiver (WDM 1310) |
| ■ 8330-165X MINI GBIC 1000LX (LC/10km) Transceiver | ■ 8330-187 LTSFP-1000BX-20KM Transceiver (WDM 1550) |
| ■ 8340-0591 MINI GBIC 1000LHX (LC/40km) Transceiver | ■ 8330-180 LTSFP-1000BX-40KM Transceiver (WDM 1310) |
| ■ 8330-166 MINI GBIC 1000XD (LC/50km) Transceiver | ■ 8330-182 LTSFP-1000BX-40KM Transceiver (WDM 1550) |
| ■ 8330-169 MINI GBIC 1000XD (LC/60km) Transceiver | ■ 8330-181 LTSFP-1000BX-60KM Transceiver (WDM 1310) |
| ■ 8330-167 MINI GBIC 1000ZX (LC/80km) Transceiver | ■ 8330-183 LTSFP-1000BX-60KM Transceiver (WDM 1550) |
| ■ 8330-170 MINI GBIC 1000EZ (120km) Transceiver | ■ 8330-184 LTSFP-1000BX-80KM Transceiver (WDM 1490) |
| ■ 8330-168 MINI GBIC 1000T (100m) Transceiver | ■ 8330-185 LTSFP-1000BX-80KM Transceiver (WDM 1550) |
| ■ 8330-188 LTSFP-1000BX-10KM Transceiver (WDM 1310) | ■ 8330-262D MINI GBIC 2.5G 850nm VCSEL (LC/0.3km) |

| | | | |
|--------------------|--|--------------------|--|
| Transceiver | | | |
| ■ 8330-263D | MINI GBIC 2.5G 1310nm FP (LC/2km) Transceiver | ■ 8330-201D | 10G Base SFP* , Single-mode(20km) Transceiver (WDM 1330) |
| ■ 8330-265D | MINI GBIC 2.5G 1310nm DFB (LC/15km) Transceiver | ■ 8330-202D | 10G Base SFP* , Single-mode(40km) Transceiver (WDM 1270) |
| ■ 8330-193D | 10G Base SFP* SR, Multi-mode (LC/300m) Transceiver | ■ 8330-203D | 10G Base SFP* , Single-mode(40km) Transceiver (WDM 1330) |
| ■ 8330-194D | 10G Base SFP* LR, Single-mode (LC/10km) Transceiver | | |
| ■ 8330-200D | 10G Base SFP* , Single-mode(20km) Transceiver (WDM 1270) | | |

All SFP ended with D are with Diagnostic function

Lantech Communications Global Inc.

www.lantechcom.tw
info@lantechcom.tw

© 2020 Copyright Lantech Communications Global Inc. all rights reserved.
The revise authority rights of product specifications belong to Lantech Communications Global Inc.
Lantech may make changes to specification and product descriptions at anytime, without notice.